NASA TECHNICAL MEMORANDUM

NASA TM - 82436

ATMOSPHERIC ENVIRONMENT FOR SPACE SHUTTLE (STS-1) LAUNCH

+ABM 3533

By D. L. Johnson, G. Jasper, and S. C. Brown Space Sciences Laboratory

July 1981

NASA

George C. Marshall Space Flight Center Marshall Space Flight Center, Alabama

JOHN F. KENNEDY SPACE CENTER LIBRARY, DOCUMENTS DEPARTMENT REFERENCE COPY

FEB 0 3 1982

		CHNICAL REPORT STANDARD TITLE PAGE
[i	REPORT NO. 2. GOVERNMENT ACCESSION NO.	3. RECIPIENT'S CATALOG NO.
	NASA TM - 82436	
4	TITLE AND SUBTITLE	5 REPORT DATE July 1981
1	Atmospheric Environment for Space Shuttle (STS-1) I	L
1	11th opposite Living and the Lipide State (212 1)	
7	AUTHOR(S)	8. PERFORMING ORGANIZATION REPORT #
ľ	D.L. Johnson, G. Jasper, and S.C. Brown	
9.	PERFORMING ORGANIZATION NAME AND ADDRESS	10. WORK UNIT NO.
	Grange C. Manghall Space Elight Center	
	George C. Marshall Space Flight Center Marshall Space Flight Center, Alabama 35812	11 CONTRACT OR GRANT NO.
1	marshan space riight Center, Alabama 55612	
		13. TYPE OF REPORT & PERIOD COVERED
12	SPONSORING AGENCY NAME AND ADDRESS	Technical Memorandum
1	National Aeronautics and Space Administration	1 ecimical memorandum
1	Washington, D.C. 20546	
		14 SPONSORING AGENCY CODE
15.	SUPPLEMENTARY NOTES	
	Prepared by Space Sciences Laboratory, Science and	Engineering
	The property of the second sec	
18.	ABSTRACT	
	This report presents a summary of selected atmos	pheric conditions observed near
	Space Shuttle STS-1 launch time on April 12, 1981, a	
	Values of ambient pressure, temperature, moisture, g	
	(cloud), and winds aloft are included. The sequence o	
	vertical wind profiles is given in this report. Also pro	
	dynamic parameters measured at the surface and aloft	
	area. Final meteorological data tapes for STS-1 vehicle	e ascent, and SRB descent have
1	been constructed which consist of wind and thermody	
	The STS-1 ascent meteorological data tape has been of	constructed by Marshall Space
	Flight Center in response to Shuttle task agreement	No. 989-13-22-368 with
	Johnson Space Center.	
Ì		
	NAS	A JOHN F. KENNEDY SPACE CENTER
	3 1.	772 00004 2215
17	KEY WORDS 18 DISTRIBU	TION STATEMENT
	STS-1 Launch Atmosphere Summary	
	Pressure	
	Temperature	
		sified — Unlimited
	Winds Winds Aloft	
	Clouds,	Brown
	SRB Descent Atmospheric Summary	VSUOVIV
19.		21 NO. OF PAGES 22. PRICE

Unclassified

Unclassified

49

NTIS

ACKNOWLEDGMENTS

The authors wish to thank Dr. Greg Wilson and Dr. James Arnold of the Environmental Applications Branch, MSFC, for their help in extracting synoptic weather data and satellite cloud photographs that are used in this report. Also, special thanks to Messrs. Wade Batts and Joe Willett of Computer Sciences Corporation for their assistance in processing all the upper air data used in producing the STS-1 final meteorological data tapes.

TABLE OF CONTENTS

		Page
I.	INTRODUCTION	1
II.	SOURCES OF DATA	1
III.	GENERAL SYNOPTIC SITUATION AT LAUNCH TIME	2
IV.	SURFACE OBSERVATIONS AT LAUNCH TIME	2
V.	UPPER AIR MEASUREMENTS	2
	A. Wind Speed	3 3 3
VI.	CONCLUSION	4
REFE:	RENCES	42

LIST OF ILLUSTRATIONS

Figure	Title	Page
1.	Surface weather map at launch of STS-1	33
2.	500 mb map at launch of STS-1	34
3.	GOES SMS-II infrared imagery of cloud cover at launch time of STS-1 (1200 Z, April 12, 1981)	35
4.	Enlarged view of GOES SMS-II visible imagery of cloud cover with exhaust trail visible during launch of STS-1 (1200 Z. April 12, 1981)	36
5.	Scalar wind speed and direction at launch time of STS-1	37
6.	STS-1 pre-launch/launch Jimsphere-measured in-plane component winds	38
7.	STS-1 pre-launch/launch Jimsphere-measured out-of-plane component winds	39
8.	STS-1 temperature profile versus altitude for launch (left) and SRB descent (right)	40
9.	Scalar wind speed and direction for SRB descent	41

LIST OF TABLES

Table	Title	Page
1.	Systems Used to Measure Upper Air Wind Data for STS-1 Ascent	5
2.	Surface Observations at STS-1 Launch Time	6
3.	KSC Pad 39A Pre-launch through Launch Meteorological Measurements	7
4.	STS-1 Final T+O Ascent Meteorological Data Tape	8
5.	STS-1 Final SRB Descent Meteorological Data Tape	25
6.	STS-1 SRB Descent-Impact Surface Ship Observations	32

TECHNICAL MEMORANDUM

ATMOSPHERIC ENVIRONMENT FOR SPACE SHUTTLE (STS-1) LAUNCH

I. INTRODUCTION

This report presents an evaluation of the atmospheric environmental data taken during the launch of the Space Shuttle/STS-1 vehicle. This Space Shuttle vehicle was launched from Pad 39A at Kennedy Space Center (KSC), Florida, on a bearing of 60° east of north at 1200:04 (0700 EST) on April 12, 1981.

This report presents a summary of the atmospheric environment at launch time (T+O) of the STS-1 together with the sequence of prelaunch Jimsphere measured winds aloft profiles from L-13 h through liftoff. The general weather situation for the launch and flight area is described, and surface and upper level wind/thermodynamic observations near launch time are given. Surface and upper level wind/thermodynamic parameter measurements are also presented for the SRB descent/impact analyses.

Previous MSFC-related launch vehicle atmospheric environmental conditions have been published as Appendix A of individual MSFC Saturn Flight Evaluation Working Group reports [1]. Office memorandums have been issued for pr vious flights giving launch pad wind information. A report has also been published [2] which summarizes most launch atmospheric conditions observed for the past 155 MSFC/ABMA-related vehicle launches through SA-208 (Skylab 4). A report summarizing only ASTP launch conditions is presented in Reference 3.

II. SOURCES OF DATA

Atmospheric observational data used in this report were taken from weather maps made by the National Weather Service, plus all available surface observations and measurements from around the launch area. Upper air observations were taken from balloon-released instruments sent aloft from Cape Canaveral Air Force Station (CCAFS) and from the ship Gen. H.S. Vandenberg in the Atlantic off the Florida Coast. High-altitude winds and thermodynamic data were measured by the Loki Dart and Super Loki rocketsondes launched from the CCAFS. Table 1 presents a listing of systems used to obtain the upper level wind profiles used in compiling the final ascent meteorological data tape. Only the ship-launched omegasonde-rawinsonde, Loki Dart and Super Loki rocket data were used in the upper level atmospheric regions for the construction of the final SRB descent/impact meteorological data tape. Data cutoff altitudes are also given in Table 1.

III. GENERAL SYNOPTIC SITUATION AT LAUNCH TIME

A ridge of high pressure over the Kennedy Space Center area during launch time was analyzed. Surface winds were lightly easterly. Temperatures were warm, and visibilities were slightly obscured by light fog. Figure 1 gives the surface weather map at the time of launch. Figure 2 shows the wind flow at the 500 mb level. Light northeasterly winds dominated the flow aloft over the Kennedy Space Center region.

The cloud bands were well northwest and southwest of the Cape, as depicted in Figure 3. Figure 3 is the GOES east (SMS-II) infrared satellite picture taken during launch. Figure 4 shows the contrail of the Shuttle after launch as seen by GOES east (SMS-II) visible satellite photograph. The directional change of the contrail was attributed to wind shear in the upper levels of the atmosphere.

IV. SURFACE OBSERVATIONS AT LAUNCH TIME

Surface observations at launch time for selected KSC locations are given in Table 2. Included are pad 39A, Shuttle runway, and CCAFS balloon release station observations. Neither precipitation nor lightning was observed at launch time. From in-cabin motion pictures the vehicle appears to have passed through the high, thin cirrus clouds during ascent.

Table 3 presents Pad 39A wind data along with other standard hourly meteorological measurements and sky observations for the 8 hours prior to launch of STS-1. Values for wind speed and direction are given for the 84 m (275 ft) FSS reference level and 18 m (60 ft) pad light pole level.

V. UPPER AIR MEASUREMENTS DURING LAUNCH

The FPS-16 Jimsphere (1215Z), GMD rawinsonde (1212Z), Loki-Dart rocketsonde (1430Z) and Super-Loki rocketsonde (1330Z) systems were used to measure the upper level wind and thermodynamic parameters for STS-1 launch. At altitudes above the rocket-measured data, the Global Reference Atmosphere (GRA) (Ref. 4) parameters for April KSC conditions were used. A tabulation of the STS-1 final meteorological data for ascent is presented in Table 4 which lists the wind and thermodynamic parameters versus altitude. A summary of parameters is given in the following paragraphs.

A. Wind Speed

At launch time wind speeds were light, being 6.0 f/s (3.6 kn) near the surface and increasing to a maximum of 98.0 f/s (58.0 kn) blowing from 250°. The maximum occurred at an altitude of 44,300 ft (13,503 m). This maximum wind speed was near the 50 percentile level for April, with lower levels being generally lighter than the April mean speeds. The winds decreased above the 50,000 ft altitude and then became stronger again at much higher levels, as shown in Figure 5. The overall maximum speed was 167.0 f/s (98.9 kn) at 212,000 ft (64,618 m) altitude.

B. Wind Direction

At launch time the surface wind direction was from the east south-east (120°) and remained southeasterly up to 4,000 ft when directions became east northeast. Wind directions stayed this way until a switch to westerly winds occurred above 19,000 ft and persisted to 60,000 ft. Figure 5 shows the complete wind direction versus altitude profile. As shown in Figure 5, wind directions became quite variable at altitudes with low wind speeds.

C. Prelaunch/Launch Component Winds

The upper air pattern described in Section 3 produced winds aloft near monthly mean values except for the weak headwind components to about 16,000 ft. The in-plane and out-of-plane wind components taken during the 13 hours prior to launch by the FPS-16 Jimsphere system are presented in Figures 6 and 7, respectively. Monthly mean component speeds are indicated by dashed lines in the figures. There were no significant changes in the profiles during this prelaunch/launch time period.

D. Thermodynamic Data

The thermodynamic data taken at STS-1 launch time consisting of atmospheric temperature, dew-point temperature, pressure, and density has been compiled as the STS-1 ascent meteorological data and is presented in Table 4. The associated thermodynamic data taken in support of the SRB descent has also been assembled as the STS-1 SRB descent/impact meteorological data and is presented in Table 5. The vertical structure of temperature for both STS-1 ascent and for SRB descent is shown graphically versus altitude in Figure 8.

E. SRB Upper Air and Surface Measurements

As has been mentioned in earlier paragraphs, an SRB descent meteorological data tape has also been constructed which consists of data taken from the Omegasonde-Rawinsonde system (1603Z) aboard the USNS Vandenberg, which was stationed off the coast in the Atlantic Ocean. The CCAFS measured Rocketsonde data, and the GRA model data, were used at altitude levels above the measured Omegasonde data. The tabular values for the SRB descent meteorological tape are presented in Table 5, with wind speed and direction profiles presented in Figure 9. Figure 8 gives the vertical temperature profile.

The surface-ship meteorological and oceanographical observations taken close to STS-1 SRB impact are presented in Table 6.

VI. CONCLUSION

The T+O atmospheric summary for the NASA Space Shuttle/STS-1 launch and SRB re-entry is presented in this report.

TABLE 1. SYSTEMS USED TO MEASURE UPPER AIR WIND DATA FOR STS-1 ASCENT.*

			Portion	Portion of Data Used	Used	
	Release Time	Time	Start	ť	End	
Type of Data	Time (UT) (h:min)	Time After T+0 (min)	Altitude m (ft)	Time After T+0 (min)	Altitude m (ft)	Time After T+0 (min)
FPS-16 Jimsphere	12:15	15	ů,	15	17 374	74
Rawinsonde	12:12	12	17 678	02	(57 000) 27 127	101
Loki-Dart Rocketsonde	14:30	150	62 484	150	27 432	171
Super-Loki Rocketsonde	13:30	06		06	62 789	91
*Omegasonde-Rawinsonde	16:03	243	(0)	243	(206,000) 24,384 (80,000)	223

*The Omegasonde-Rawinsonde was released from the USNS Gen. H.S. Vandenberg to measure the upper atmosphere for SRB descent/impact analyses.

TABLE 2. SURFACE OBSERVATIONS AT STS-1 LAUNCH TIME

							S	Sky Cover		Wi	Wind
Location ^b	Tume After T-0 (min)	Pressure, N/cm ² (psia)	Temperature, K (°F)	Dew Point K (°F)	Relative Humidity (%)	Visibility km (miles)	Cloud Amount (Tenths)	Cloud Type	Height of Base Meters (ft)	Speed f/s (kn)	Direction (deg)
NASA Space Shuttle Runway.	0	10.237	288.6 (58.0)	285.9	92	16 (10)	4	ci	10363	3.4 (2.0)	100
Winds Measured at 10.4 m (34 ft)											
CCAFS ^d Surface Measurements	12	10.234	290.2	289.1	93	•	,	ı	,	6.0	120
Pad 39A Lightpole	0	(14.84) 10.180 ^f	(63.0) 294.3	(61.0)	83	,	,	ı	,	3.6 11.8 ^c	125 ^C
SE 18.3 m (60.0 ft) Pad 39A FSS	0	(14.77)	(70.0)	(64.0)	,	,	ı		ı	(7.0)	120°
(Top-SE) 83.8 m (275 ft)										(9. 1)	

Pad 39A Camera Site 3 barometric pressure instrument appeared to be reading too low. Therefore, the KSC Shuttle runway station pressure of 10.234 N/cm² would be more appropriate as the T + 0 pad atmospheric pressure measurement, to be applied at 14 ft above MSL.

b. Altitudes of measurements are above natural grade.

c. 1 min average prior to T + 0.

d. Balloon release site.

e. PAD 39A thermodynamic measurements are taken at ~ 1.2 m (4 ft) at camera site #3.

f. Station pressure value.

*Reduced to mean sea level.

Martin Market and Control of the con

TABLE 3. PRE-LAUNCH THROUGH LAUNCH KSC PAD 39A METEOROLOGICAL MEASUREMENTS*

	Hourly A	Hourly Atmospheric Measurements	Measu	rements				Sk _f Condition			:
	1			275' Level (SE)**	evel	60' Level (SE)**	vel		Total		I
12 April 1981 Time Z	remp. (°F)	Dew Pt. (°F)	ж ЭЭ	WS Kt	WD°	WS Kt	WD°	Clouds	Sky	(mi:)	Other Remarks
0400	22	62	2.2	6	070	2	060	Thin scattered at 34,000 ft	4/10	10	
0200	02	61	2	97	010	Ф	100	1/10 AC at 15,000 ft, 4/10 thin CS at 34,000 ft	4/10	10	Patches Ground Fog
0090	70	99	92	10	070	9	100	1/10 CU at 2,100 ft, 4/:9 thin CS at 34,000 ft	5/10	10	Patches Ground Fog
0020	70	61	*	92	060	œ	011	1/10 SC at 3,500 ft, 3/10 CS at 34,000 ft	3/10	10	Patches Ground Fog
0800	20	61	74	6	060	œ	110	1/10 CS at 34:000 ft	1/10	01	Patches Ground Fog
0060	22	62	92	6	060	r-	110	Clear	0/10	10	Patches Ground Fog
1000	89	61	82	6	080	•	011	Clear	0/10	10	Patches Ground Fog
1100	89	62	08	øs.	060	4	140	1/10 CU at 2,000 ft, 4/10 Ci at 34,000 ft	4/10	-	Patches Ground Fog
T-0***1200	70	64	82	6	120	7	125	4/10 Ci at 34,000 ft	4/10	16	Patches Ground Fog

* - Hourly verbal observations from CCAFS

^{** - 10} min mean from instrumentation on SE side of pad 39A. Hourly verbal estimates from CCAFS

^{*** -} T+O PAD Winds from KSC strip charts ($^{\circ}$ 1 min average before T+O) T+O PAD thermo parameters from MSFC-HOSC data bank ($^{\circ}$ 1 min average before T+O)

TABLE 4. STS-1 FINAL T+0 ASCENT METEOROLOGICAL DATA TAPE

1;

0000		ENTINE ORTE	SEMPLIAN UME	PRESSURE	DENSITY	NIOS NIO
	15 T /SE C)		17.0	CAILLIBARS .	158AM/M31	
	95	77	9 (10404	PU+1221+	6° C7
001000	50	521	N. L.	*0*0201	10-121-	** ST
007000	110	121	4.61	**************************************	1204404	1.51
	7.5		47.	10.1101.	\$0.007T	15.5
				1004-00	#D+4044	15.4
	022) en	10.2	1002-04	1191404	15.2
00000	025	136	8.00	. 9990-03	.1186.04	15.1
- 0000 no	020	137	10.7	.9954.03	.1101-04	15.0
004000	050		10.0	NO+6166.	.1176-04	1.5
000100	023	132	19.1	. 9665+03	.1171.04	14.6
001100	021	143	10.0	.9850+03	-1168+04	14.7
007100	610	139	10.5	.9015+03	.1165-04	14.5
001300	020	M M 1	10.2	.9780+03	-1162-04	7.5
001400	023		17.9	.0.5074.	10.6511.	19.3
001200	021		17.7	.9711+03	1156-04	7.91
001600	610	P. C.	F • 2 P	50.01.00	103404	
	# P P P P P P P P P P P P P P P P P P P	1 T	1.71	940940	40 - N - C - C - C - C - C - C - C - C - C	
	570	2 4 5		70 74 74 8	40444	7-11
	120			70.FLR.		5 5 5
002100	020		0.91	1.950e+	*D+0**	
002200	024	143	15.6	.9472+03	.1135+04	7
002300	022	1 + 1	15.6	. 9438+03	-1132-04	
005400	022	130	15.4	.9404-03	.1129+04	,,,
002200	100	141	15.2	. 9470	-1126-04	
004400	100 mm)- (A-		10 - 10 - 10 - 10 - 10 - 10 - 10 - 10 -	*0.5711.	
002800	023	P	5.0	.9270+03	.1116.04	1.2.1
00500	025	181	N - P R	. 9237+03	. 1113+04	11.9
00300	022	162	14.1	.9204.03	.1110-04	11.
001100	021	356	14.2	.9171+03	.1106.04	01
003500	120	n e	M · Fi	NO+8814.	102-04	
003500	A10		P • P •		*D****	
		D (C • F • •	F0+5404	******	
003200				10000000000000000000000000000000000000	**************************************	
003700	013	156	7.0	.8975+03	.1082.04	3.
00 36 00		144	19.9	. 8943403	.1078-04	F-1
00 33 00	: 30 0	102	15.0	.8911+03	.1074.04	•
00000	600	8 60	15.1	.8879+03	.1070+04	•••
001100	600	P 1	15.1	NO+2+00.	1067-04	
207.00	100	\$20	19.1	CO.6198.	*D * 5 90 7 •	
004300	200	- 100 - 100	15.2	NO+FELS.	*0+650T*	
	110		13.6	CD-26/8.	*D*660**	
004200		D F W	y	50.17/00	*****	7.1.
		- 6	7.07	50.049.	7000	
001400		B 6 50	7.61	00.000.	40000	
	220	• 0	2 · 67	50-1798	10.010	h = 7

TEOROLOGICAL DATA	ITA TAPE BIND SPEED	WIND DIRECTION	TEMPERATURE	PRESSURE	DENSITY	DEW POINT
(7.1)		1930)	(DEG C)	IMILLIBARSI	(GRAF/HS)	(DE6 C)
00500	019	000	15.3	. 6566+03	.1032+04	-2.2
005100	024	190	15.2	.8535+03	.1029.04	2. 2-
005200	024	790	15.1	.0504-03	.1025+04	-2.3
002300	023	0.0	15.0	.04746.	.1022+04	-2.3
008400	025	075	14.9	.0+8440	.1019-04	-2.4
008800	028	910		. 04 L 40 .	.1016+04	-5.5
007500	\$20	*	0.51	50+285 9 •	*0 *7 10 1 *	6.71
002700	025	M 4	S	. 6352+03	*D**DUT*	-2-5
100000		770		PG+0000	1003+04	-2.6
	027	210	10.2	. 8263-03	. 994403	-2.1
004100	025	980	14.2	.8233.03	. 9954-03	-2.1
008200	020	010	10.2	.8203+03	. 9923+03	9.7
006300	020	8 9 0	11	. 6174+03	10-9006	9.2-
- 004900	620	990	H • 61	10-5-10-	20+23-67	5.5-
005900	250	7 9 0		60+6178•	E C - D T - C - C - C - C - C - C - C - C - C -	
	9 4 6 6				MC+Part P	-2.3
	777			10-0200°	9714-03	-2.3
	0.00	120	0.41	. 7999+03	.0.0994	-2.5
	5 6 7 6 7 6 7 6 7 6 7 6 7 6 7 6 7 6 7 6	023	70.0	.7970+03	.9645+03	-2.2
001100	031	210	13.8	. 7941.03	.9618+03	-2.3
007200	033	000	13.6	.7913-03	.9591-03	-2.5
0073ng	150	• 10	13.3	NO++001	NO+1956	9.2-
00 14 00	nno	970	1001	ND+959/*	10.016h	1.7-
00 00 00 00 00 00 00 00 00 00 00 00 00	2 C C C C C C C C C C C C C C C C C C C		12.4	.7759.03	. 948 VOIS	0.0
		6	9 6	7771+04	10+940	1.5-
	031	000	12.2	. 7743 -03	. 9429-03	-3.2
004400	010	010	12.0	.7715+03	.9402+03	-3.4
00000	033	M 00	11.0	.7687-03	. 9376+03	ç.
00100	032	\$ 0 0	11.6	1659+03	**************************************	9 1
008280	032.	6 C		LD+12.07.	20-A176.	
	250			10+848C	.9262+03	6.5-
007200	033	07.5	11.0	.7548-03	.9234+03	-3.0
009600	035	910	10.0	.7520+03	.9206+03	0
004100	034	* 40	10.6	NO + NO 82.	.9178+03	r
000000	900	073	#*O#	* 0 + 0 0 t / ·		7051
00400	920	7	10°5	. 7412-03	. 0095+03	
	7 6				10+0400	1.4-
004100	032	* S C C C C C C C C C C C C C C C C C C		1387+03	. 9042+03	-5.0
004300	032	6 90	9.8	.7330+03	.9016-03	M*S-
00100	034	• • • •	9.3	, 7303+03	50+D46#.	9 1
008600	034	072	9.1	.7277+03	. 896 14 + 0 3	• · ·
009600	031	• 90	•	-7250+03	50+6549	7.0
004400	034	290	9	50-527-	40040 apple	
00%00	035	A F	•	100011		-1.2
004400	150	2 2	y .	73.3.4.	•	1

015000 01510 015100 015300 015300 015500 015500 015000 016100 016100		10F6 5	10E6 C)	. S919-03	. 7620+03 . 7593+03	-16.
		0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0			. 7593-03	-17
		036	-2.0	. 446740		
		625 625 625 625	0.61	4874-03	. 7567-03	-17.
	0017 0018 0018 0018 0018	037	1.6-	.5852+03	.7541.03	-17.1
	000 010 010 010 010 010 010	- MO	-3.2	.5829+03	.7515+03	-18-
	0115 0115 0115 0116 0116		20 e 00 -	\$0+L0 65	50+69a.	:
	, 2000000000000000000000000000000000000	S 20	#*M-	.5765+03	. 7464+03	
	, 2000000000000000000000000000000000000	010	in i	.5762+03	50.00.00	
015900 016000 016100 016200 016300 016400	20000 20000 20000	017	9.51	NO.0116	50.754.	
016100 016100 016200 016300 016400	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	100		FD+91/6*	**************************************	
016100 016200 016400 016400	- e s	110	P • • • •		40+1001.	-02-
016500	5 6 6			\$00 F C B F S	10,000	-20-
016500	6 6	2 6	7 4	F C 4 F 4 F 4 F 4 F 4 F 4 F 4 F 4 F 4 F	* E + E + C + .	-20.4
014500			7 4	10+10+10+10+10+10+10+10+10+10+10+10+10+1	7256.03	-20.6
			244	NO+0055	1212+03	-50.
201710			1 PF 1	10+9955	1206+03	-21-
	, e	: c		5545+0	.7161+03	-21.
	250			.5523+03	.7155+03	-21.
2000	: 5	342		.5502+03	. 7130-03	-21.
000110		068	9.7	.5481.03	.7105+03	-12-
D17100	10	500	•	.5460+03	.7063+03	-22-
017200	10	321	-5.0	. S439+03	. 7062-03	-55.
017300	011	517	m.,	.5418+03	. 70404	-22-
00110	470	324	មា (10+2+M6*	. 701 9+03	. 22-
01 7500	916	e de la companya de l	P. 6-	NO+9/NO+	50+1650°	•22•
017600	716	1110		20+0020•	70.07.00	
017700	25	215	1.9-	*******	**************************************	
	75	¥16		*******	F G 4 F 4 G 4	
	510	5 C C		10+445.	6892+03	-23
0000		225	0°2-	.5252+03	.6870-03	-23.
		9 7 7	7.1-	.5231-03	.6646+03	-24.
		. C	- 7	5211+03	.6827.03	-24.2
	•10	125	-7.6	.5191+03	.6805+03	-54.
	•10	108	-7.8	.5170+03	.6784-03	9.42-
010600	013	313	0.0-	.5150+03	.6763-03	-24.
014790	010	315	-1.2	.5130.03	.6741+03	-25.0
01800	110	102	•	.5110+03	.6720+03	1.62-
016900	010	303	0·6-	50+0405*	. 667 4-03	57
0006:0	60	296	9	.50+0.403	50+0-04·	
014100	010	274	•	£0+0505•	50+00+4 50+00+4	-25-
019200	200	26.3	7.61	co-Troc-		
01010	S 00 0	251		50 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	70+700	-26.3
001610	200	262	•	700000		- 36-
019500	202	259	1.01-	50+7144	*D.D.D.D.	
-	.	546	7.01	50.7548.	10-1909	***
019760	010	238	9.DI-	. 4932-03	60.469.	
090410	010	248	4.01-	50.5144	CO. C 7C.	

AL TITUDE	NINO SPFED	VIND DIRECTION	TEMPERATURE	PRESSURE	DENSITY	NEO V30
1.	(F1/5EC)	930			CENTAL SO	(1910)
	035		-			
	***		•	50.017.	50-1100	
- 002010	033	270	7.55	. 7055-03		
			:,			
				40.40.4	70.07/0.	
				F C + F C + F		
01010	450	440		FG+7464	10-04-4	5.4
004010	410			10-11-1	10+1140	1.1
000010	0.50	. 40		10-010-9	1001140	
011000	980	8 40	, P-	10-10-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	10 - 10 CO	-
011100	030	062	\$0.00 \$0.00	E0+6844	. 8561+03	1.5-
011200	035	073	8.5	.6833.03	. 8537-03	-4.1
011300	036	\$ 90	9.0	.6404-03	. 8512+03	-4.5
011400	035.	0.00	•	.6783.03	.0407-03	-9.5
011500	033	• *0	:	.6757-03		
011400	800	**0	n••	.6732+03	10.01.0.	***
01110	en o	010	~ · ·	. 6707+03	NO+#170	•
00110	032	• • • • • • • • • • • • • • • • • • •	•••	. 6682-03	10.0000.	-4.5
011400	033	6.0	• · · ·	10-1299	.0.346	-4.5
000210	100		**************************************	. 6632-03	1001000.	•
	• • •		3.6		50,0150	
007710	0.00	7.5	0.0	70+7000	424400	
01240	420	2.4	2.5		10-11-0	
012500	120	0.0	2.5	F0-6059*	.8217+03	•
012600	026	100	2.1	.6485-03	. 6192-03	-10.0
012700	023	010	1.0	.6460.03	.0140-03	-10.1
012800	#2D	**0	1.1	. 6436+03	. 614 3-03	-10.2
012900	052	270		.6412+03	10.410.	-10.2
			•	000000		
01110					20×1000	7.01.
013300	•10	26.7	: •	10.45 E	. 6024+03	-10.
013400	•10	910	•	.6292.03	. 0 0000+03	1:11-
013500	\$10	8 00	••	.6266 +03	. 1917-03	-11.3
013600	010	000	:	.6244-03	. 1950.03	•: = -
013700	017	6.00	m :	.6220+03	1930+03	-11-
	•	9 4 6 6	un e	ND+1016.	50-101	12:0
		0 00		F0+04+4-	PC+1461	4.51-
				000000		
014100			7.1.	10.1714	7812-03	1.11-
001410	110			PE + CROS	7788+05	-15.7
004400	100			.6057+03	1764-03	-14.2
014500	210	0 4 6	6-1-	10.4034	1739.03	-14.6
0100		440		101104	2715.03	-15.0
	210	200	-2.5	MO-666	7691+03	š
	110	926	-2.1	50+5+03	.7667+03	-15.9

DEW POINT	TOES C				82-						-29.							7.00															7.66.							* # P					135		2.95	
0645177	Z W/WY du		20.5949	10.5449.	.6426+03	.6407-03	.6387+03	. 6 36 8+03	50+6 #E 9 .	.6330+03	.6311+03	.6292+03	.6273+03	CD+CC74*	0.9629	£0.9120.		101019			50-97[0.				10.2604.	10.5.04.	E0+4842.	5978-03	.5959+03	. 5941+03	. 5923.03	.5403+03	10.1000.		5826.0	.5607+03	.5787+03	.5768+03	.5749+03	.5730+03	.5713.03	.5695+03	5678.0	. 5660.03	.5642+03		.5604.03	CD+U6555*
	AMTLL TRADE.	4874+03		FD+97-97	.4817.03	.4798-03	.0.178.03	10.484.	. 4741.03	722.03	. 4703+03	0	NO+9994	70-795	50+029h*	50+0144	SOLTAGE.	10.5734 D	50+565·	50.056.	NO+0150.	50.0054	50+78**	10.00 ave.	10.00 pp.	10 · 0 · 0 · 0 · 0 · 0 · 0 · 0 · 0 · 0 ·	NO - 10 11 11 11 11 11 11 11 11 11 11 11 11	6374.03	.4356+03		. 4321+03	F0+F0F+	10.5854.	40.00	20.00.21.	4216-03	.4199.03	.4181.03	.0.4914.	10-2-14-	. 4130.03	. 4113-03	ED+9604	. 4079-03	.4062+03	.4046.03	50+4204	1012101
TEMPERATURE	10 8000		-1	0.11-	77.0	-12.4	-12.6	-12.9	1.81-	-13.4	-13-6	-13.4	2 - 1 - 2	•	V. B.I.	D-61-	2·6[-	10 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1	10 · · · · · · · · · · · · · · · · · · ·	7 - 4 - 1	M - 0 - 1	9.91	D .	1.21-	P1 4 P	9 - 2 - 1			-10.6	-10.0	-19.1	-19.3		0 0 0	A - A - C - C - C - C - C - C - C - C -	102-	-20.5	-20.1	-20.9	-21.1	-51.4	-21.6	-21.9	-22-1	-22.4	-22.7	-55.0	
MOTEURIC ONLA	1980	920	24.5	016	243	233	236	260	240	549	256	255	27.7	522	274	216	102	102	912	192	288	192	062	102	802	907	7 7 7	270	276	275	27.1		278	987	- P - C	242	27.2	271	261	292	261	250	262	261	592	265	264	
TAPE MING SPEED	111111		. 6		900	200	400	900	900	200	900	*00	600	400	600	900	A 00	010	910	110	010	50	S 10	. 10 				55	\$10	010	910	***	970	•	910		7	110	*10	910	. 510	*10	016	015	015	015	210	
METEOROLOGICAL DATA	1117					020400	02020	050600	020700	020600	020900	05100	051100	02120	021300	021400	051200	021600	02120	008120	021900	02200	022100	022200	022300	004720	022500	022700	022800	022900	023000	023100	023200	023300	023400	2000	021100	023000	023900	054000	024100	024200	02+300	05+400	024500	02*400	024700	

104	(2 930)		-36.8	-36.9	-37.1	-37.2	-37.4	-37.6	-37.7	-37.9	-38.0	-38-2	4.42.		- 47			7.65	M + M +	-34.5	-39.7	-20.0	-40-1	0-3	-40.5	-40.7	40.0	-41.1	7.77	•• 1 •-	9.1	-42.0	-42.2	-42.4	2.7	-42.9	-43.2	# · M ·	-43.1		-44.2	7.72	C. 8 8 -	• · • · ·	ŝ	8	-45.7	-42.4	-46.2	#* 9 *-	-46.7	-46.9	
0ENS1 FV	IBRAH/H3)	.5556+03	.5537+03	.5516.03	. 5 500.03	.5481+03	*62.	. 5 4 4 4 0 3	.5425+03	.5407+03	. 5388.03	10+04N		NC+PRING.			50,040	50.0025	0 • 2 9 2	10.7 £ 5.	. \$227.03	.5209+03	.5191-03	.5174.03	.5158+03	. S.la.1+0.3	.5124+03	.5107.03	. BO 1 + D 3	.\$074.03	. \$050+03	. 504 1+03	.5025+03	. 5010+03	KO+464.	. 4974-03	. 4964.03	NO-0-6-	. 4 5 3 4 + 0 3		.4904.03	. 4 86 9 • 0 3		.4859+03		.4629+03	. 4814.03	. 4 900+03	. 4 765-03	.4770.03		.4741.03	
PRESSURE	CAILLIBARS	. 3979-03	. 3963-03	. 3946.03	.3930+03	.3914.03	.3897+03	.3681+03	. 3865+03	NO+6448	E0+11-05	NO+2145	FC+1C42		FC-04F-			. 37 56 . 0 3	.3722-03	. 3706 -03	.36+1+03	. 36 75 + 0 3	.3660+03	. 3644.03	1629.03	NO+845	NO+8050	10.18.04.	3568	3553	. 35 38 + 0 3	. 3523+03	.3576+03	3103	.3478.03	. 346 3+0 3	.3448-03	. 34 3 3 + 0 3	.3419+03	. 3404+03	.3389+03	.3375+03	. 3361+03	.3346.03	.3331+03	.3317-03	.3303+03	3248.0	. 32 74+03		3246.	. 32 32 + 03	
TEMPERATURE	(066 C)	-23.7	-23.0	-24.1	-24.3	-24.5	-24.6	-24.8	-25.0	6.26.	-25.4	125.4		0.46			1.02	9.92-	-26.8	-27.0	-27.2	-27.4	-27.6	-27.0	-28.1	1.10-	-28.6	-28.0	2.00	-29.3	-29.8	-20.0	-33.0	-30.3	-30.4	-30.4	-31.2	-31.5	-31.0	-32.1	-32.4	-32.7	-33.0	-33.8	-33.6	-33.0	-34.2	-34.5	-34.			-35.7	
WIND DIRECTION	(930)	266	266	261	260	264	265	26.9	270	26.0	240	***		B C C				270	273	276	271	242	299	259	247	200	9 S S S S S S S S S S S S S S S S S S S	250	280	25.5	248	25.1	25.5	240	25.1	25.2	25.	255	250	250	251	249	54.9	246	243	244	241					24.5	
ž 3	(FT/SEC)	015	017	710	610	910	610	021									610	140	120	050	021	910	•10	•10	•		120	•	120	021	023	022	022	923	022	023	025	920	024	027	027	720	030	620	033	510	950	450	037	046		627	
HETEOROLOGICAL DATA	(6.1)	025000	.025100	025200	025300	025400	025500	025600	295733					001920		1.603U	004420	024500	054400	024100	024400	024900	02,1000	001220	22220					021700	024200	023400	0.000	928.00	02920	029300	00000	026500	029600	026700	02400	02820	020420	029100	029200	029300	02.600					05450	

DEN POINT	(DEC C)	-53.5	-53.0		-54.3	-54.5	-21.3	-55.1	.55.3	-55 ° 6	-55.6	-56.1	1.96.4	-56.6	-56.9	-57.2	4-7-8-4	F - K - K - K - K - K - K - K - K - K -				0.00		•	-24.3	5.65-	-89.1	0.09-	F-09-	-60.5	-04-	-	19-	-6666-	-6666-	- 2666 -	656-			.6666-			-1000	• • • • • • • • • • • • • • • • • • • •	• 6666-	• • • • • • • • • • • • • • • • • • • •	****	• • • • • • • • • • • • • • • • • • • •	.6666-	-000		• • • • • • • • • • • • • • • • • • • •
	(CE/X/29)	. 3955-03	. 3942-03	. 3424.03	.3915.03	_	* NEE 9 - 0 N	. 3976+38	•	.3850-03	.3037+03	. 3825+03	.3811+03	1798-03	3785+0	1772+01		1111			200		•		.3670-03	. 2658.03	. 3646.03	. 3633+03	. 3621-03	. 3604.03	296.0	2010	572+0	\$61.0	. 354 9+03	. 3538+03	. 3527-03	. 3515+03	•	no-no-n	;	. 3470+03	5		NO+MARN.	3.5	50+10+5·	10.5011	-	. 3369+D3	_	. 1344.03
PRESSURE	CHILIBARS	.2573-03	.2561.03	.2550+03	.2536+03	.2526.03	.2515.03	.2503+03	.2442+03	.2480+03	2469.0	245		2435+0	2424+0	241240	2177		0.000	50.4757	50.0057	.2357-03	.2346.03	.2335+03	.2324.03	.2313.03	.2302+03	.2291.03	.2281.03	.2270.03	•	.2249.03	.2238.03	.2227.03	.2217.03	.2204.03	.2196+03	.2165+03	.2175.03	9	.2154.03	.214403	.2133+03	.2123-03		0	0	.2002-03	.2012.03	•	3	.2012.03
TENPERATURE	inte co	5.94-	0.987	-47.1	-47.5	-47.6	-47.4	-46.2	-46.5	:	0.64-	:	4.01-		- 69-				\$.	2110	6 · 1 p.		-52.0	-52.3	-52.6	-52.9	-53.2	-53.4	-53.7	0.48-	N . # St .	-54.6		-55.2	-55.6	+·88-	-54.3	-56.6		-57.3	-57.6		•	•	÷	-89.0	:	-59.4	-54.1	-	-60.1	-60-
WIND DIRECTION	19101	254	253	251	254	25.7	256	255	254	254		 	25.6	246	36.		7 0 0	4 9 6	107	922	522	256	25.7	25.7	256	25.0	25.0	260	26.1	260	240	25.	242	262	260	259	25.9	263	261	26 3	292	26.1	262	292	261	26.1	261	260	259	257	260	258
TAPE WIND SPEED	17 T/SEC1	240	0.0	r *0	042	••0	**0	D#1	020	450	050	0.50					7.0	660	053		* SD	250	0.54	053	055	054	053	055	053	054	980	053	055	05.3	053	055	052	•\$0	055	054	980	053	053	053	051	055	053	052	054	980	051	150
METEOROLOGICAL NATA ALTITUDE	111	035000	001510	035200	035300	038400	035500	035600	001570			200710				200000		036200	03000	036700	003460	036400	037000	037100	037200	037300	0037400	037500	037600	037700	037800	037900	039000	038100	036200	COLUC	038400	038500	038600	038700	038800	038900	0.39000	034100	039200	039300	00%600	039500	033600	034100	008480	004680

DEW POINT	1000	-1111	-9999.	-6666-	-6666-	-1000-	-9999-	-1111	-1111	-9999.	-1110	-9499.	-6666-	.1999.	- + + + + + + + + + + + + + + + + + + +	-6666-	-6666-	-4440	-6666-	-6666-	-0460-	-4446	-9999-	-6666-	-6666-	-0000-	-6666-	-9999		• • • • • • • • • • • • • • • • • • • •	-1010	-6666-					****			.000-		0000-				0000					• • • • • • • • • • • • • • • • • • • •
DENSITY	(CBAR/RS)	. 3331-03	. 3316-03	. 3 300 • 0 3	. 3284+03	. 326 9.03	. 325 3+03	.3230+03	. 322 3+03	. 3204.03	.3192-03	.3177.03	.3163.03	0	Ö	.3121-03	.3307.03	. 30+3+03	. 30,7003	.3065+03	. 3051-03	. 3037-03	.3023+03	. 3010-03	.2996+03	.2983+03	.2969.03	.2956+03	294 3403	.2929+03	.2916+03	. 2 90 3 + 0 3	. 2 88 8 + 0 3	2874-03	. 2 65 9 + 0 3	50+5+27*	20010020	******	PC+4014	AC44540	276.04.01	2744403	2732+03		20001731) C	50-0497*	50.4797	26.5.0	50.4407.	.2635.03
PRESSURE	(MILLIBARS)	.2032.03	.2023+03	.2013+03	.2003+03	.1993-03	.1984-03	104468	. 1964-03	10-55-1.	.1945-03	. 1936.03	.1926.03	.1917-03	.1908.03	.1898-03	1004001	. 1660.03	.1871-03	.1862+03	.1653-03	. 104 3 + 0 3	.1834.03	10.9201	.1817-03	.1808.03	.1799.03	1740-03	.1761.03	.1773+03	.1764.03	.1755-03	.1747-03	.1730-03	.1730+03	.1721.03	NO+5 1/10	7 D • # D > 1 •		20 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	10.000		655+0				0.100	1623+03	0.514	50+1041+	.1599.03
TEMPERATURE	1016 C)	9.09-	9.09-	-60.7	-60.7	-60.7	-60.7		-60.	9.09-	-60.4	-60.9	-61.0	-61.1	-61.1	-61.2	-61.3	-61.4	-61.5	-61.5	-61.6	-61.7	-61.8	-61.0	-61.0	-62.0	-62.1	-62.2	-62.3	-62.3	-62.4	-62.5	-62.5	-62.4	-62.4	-62.4	E 29-	M • 69	7 P	6.64.			-62.2		162.1	0.40	> 1 Q-1		9-1-9-	-61.0	-61.1
WIND DIRECTION	(056)	259	25.9	26.1	262	260	259	260	25.0	25.7	256	252	251	253	253	255	256	255	250	251	252	254	253	256	255	257	260	261	263	26.1	259	257	757	255	255	251	253	F 62	167	167	767	707	4 M	607	E 62	n ı	250	5#8			25.1
N TAPE WIND SPEED	IF 1/5EC1	056	057	150	057	190	650	90	N 90	r 90	***	890	069	940	070	.070	070	190	280	083	190	082	003	940	082	070	710	0 0	940	710	940	640	940	070	740	003	4.00	9 (10)	2 60	7 6	260	, ,		640	9 60	200	***	960	660	• • • •	880
δ∺	(1)	04 0000	5	040200	040300	004040	040500	00000	040700	00 00 00	00000	000140	041100	041200	041300	004140	00110	041600	041703	041900	004140	042000	042100	042200	042300	042400	04.25.00	04240	042100	042800	04240	0000	04 31 00	04 3200	043300	00 % 40	043500	043400	043700		004540	2007		00710	0000		044500	009**0	004100	0000	00440

TABLE 4. (Continued)

1106		• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • •	-9999-	.4447	****	- 550	(0000)	-6660-	6666-	*******	-0000-	-6664-	-9639.		*****	-6666-	****	• • • • • • • • • • • • • • • • • • • •	*****	-	* 000 * 000				6066-	- 6666-	-6666-	-6006-	-0000-	*666-	* 000000000000000000000000000000000000			-6666-		*****	.0000-	.9996-	-0660-	*****	-0666-	•0666-		• 0606-
> 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0			C0.2907.	.2073-03	50459020	£0+450Z+	*******	50.9507.	2017-07	200	1999	.1990.03	.1982-03	.1973-03	.1965-03	.1956.03	. 1947.03	.1939+03	.1931-03	. 1922+03	1914-03	FD+9041	1697-0	704401.	******	0.779	104541.	.1847+03	.1839.03	.1831.03	.1827.03		-	20.00m.	• •	1042411	1770+03	1762+03	11755.03	.1747.03	BU-6821.	.1731.03	.1727.03	.1715+03	.170:+03	.1700.03	.1692.03
		CO. C. T.	50.1531.	.1231+03	. 1669-03	1218.03	50.7171.	100001	50.0071	PO- BENEV	11182+03	176.0	.1171+03	.1165-03	.1159.03	.1153.03	.1147+03	.1141.03	. 1136.03	.1130+03	1124-03	50+A111*	50-5121-	500/0110	50.7011.			1080+03	.1074-03	.1069.03	. 1063.03	0.00	1053-03	50+7+01-	E 0 0 E 10 E	1001101	1026+03	.1021+03	.1016-03	101010	.1005+03	.1000.03	20+6466*	.0098.07	.9847+02	.9796.02	-9746+02
		1.00	7.00-		7 · PD	5.99-				- C-		-67.7	-67.	-67.5	-67.7	-67.4	-67.9	-68.1		7.09.	5-89-	0.00		P. 0			7 2 4 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	-69.8	-69.7	-69-	-70.0	-70.1	2001	5.07-		0.00	-71-2	-71.3	-71.5	-73.6	-71.8	-71.9	-72.0	-72.1	-72.3	-72.4	-72.5
SOFT TRANSPORT	446			# P P P P P P P P P P P P P P P P P P P	97	265	997	997	271	271	266	273	27.3	268	273	27.1	214	274	27.7	201	27.8	502	276	187	002	976	0.40	267	261	257	26.	258	757	882	197	767	200	262	255	260	262	262	264	292	25.6	261	25¢
A TAPE LIND APPED	17 1/36 17	***		2 6 0		080		910	270	0,00	990	990	063	090	980	650	054	200	051	050	052	020	920	91	7 10	7 6	7 6	038	037	0.0	035	030	037		2.0	7 0	900		042	037	000	240	1 %0	U*1	# # D	# # D	8 0
METEOROLOGICAL DATA			0000		0000					000000	02 1000	051100	081200	051300	051400	051500	051600	051700	02150	006150	022000	001740	022200	004240	004750	005300	002250	052800	052900	053000	053100	053200	023200	000000	00.55		0.000	053900	02450	054100	02450	054300	024400	054500	009*50	054700	024900

TABLE 4. (Continued)

EOROLOGICAL DATA	TAPE COFFD	WIND DIRECTION	TEMPERATURE	PRESSURE	0685177	P.C. 1917.
	(F1/SEC)	(930)	(D 830)	CHILL TOARS	16747139	19.6
000500	•	392	-12.8	20-0-0	80014810	
-	ŝ	263	-72.7	20+9484	.1666+55	
055200	2,00	268	-72.7	20-1-50-	.166.00	. 4.74
	240	272	-72.6		10.0591	
001550	5	268	-12.6	20-6114-	. 1641.0	***
004840	5	275	-72.5	70+10+4·	50.854.	. 70
009860	039	276	-72.8	ND PAGE	S DON NE S	
055760	020	273	-7Z-0	70-90F4-	000000	400
055600	058	569	2.57-	20-1624		40.00
02220	020	152	6-12-	20+02-0		
000750		257	2.27-	20.2014		
084100		252	2.21.	20-0900·	1877401	. 36.
002950	20	667	6.686	-6022-02	156003	.0000
	5	200	13.3	-0074-02	1556+03	
	36		-72-1	20+05-0	.1540+03	• • • • •
		• • • •	-72-1	20+00	. 1540+03	-000-
		25.0	-72.1	. 6636+02	.1532+03	-6667.
	683	72	-72-1	.67+3+02	. 1524-03	.000
6064	9.50	26.5	-72.1	. 6746-02	.1516-03	
90000	510	270	-72.1	.8703+62	×0.0011.	****
05000	032	274	-72.6	.8264-02	NO-9557	***
00000	026	278	-73.1	.7850+02	.1367.03	
040000	020	207	-14.6	20+4447	100000	*****
041000	810	309	-74.3	.1014.02	1240+03	40 A C A 4
962298	6	336	-72.3	-6720+02	. 1 166+03	
00000	Š	100	S-69-	-6385-02	50+46D1 ·	
900430	200	250		2041/00	£044.201 •	
000590	=	190		20+5149	2006044	
00000	020		9.00	20.5406.	70-0224	
002-10	ž	9	B • MO •	20-1226	70+4490	7000
000000	22	071	0.20-	10.01AT	*******	
00010	=	S 9 0	0.101	400 A 0 A 0	**************************************	
04004	110	200			2010101	-6436
04100	5			40-1-10-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-	.6665402	
			-57.0	3905+02	.6317.02	-5445-
	200	057	9.96-	. 37 23 . 02	.5989+112	11.00.
	030	26.3	28.4	. 3550-02	.5679.02	. 466
9740	032	••	-53.6	. 3306.02	. 537 3002	55.5
000110	620	710	-50.4	. 3232+02	20.9906	***
01000	120	093	6.07	. 3006.02	20 - 064 0 -	
014080	022	215	2.4.7	20+0+62	70 + C 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
*****	6	E M		. 28 16 - 02	NO MANAGE A	8 3 6 6
00070	*	165		20.4862	20.71.11	
062000	*	## ## ## ## ## ## ## ## ## ## ## ## ##	•	20+4-66.	* * * * * * * * * * * * * * * * * * *	
00 3000	5	12 (C)		******	47 - B - R -	.000
	8			****	004	4000
0005	8	276	2.07	70.0177·	3286.02	
00010	200	600	70871	90.1.190	, , , , , , , , , , , , , , , , , , ,	

AL TITUDE	ND SPE	WIND DIRECTION	P ER AT			20
(11)	(FT/SEC)	(066)	ه	(SILLIBARS)	CONTRACTOR OF THE PROPERTY OF	(086 C)
0001 00	010	100	2.98	2049+02	20-1416.	****
0.0000	010	960	:	20+6641.	. 300000	
0006 90	022	900	nı	20.005	20.4C82.	
000040	020	A 90	n (20+60	7001497	٠.
000160	021			20+1891	20+1405	9
000260	027	021	8.71	70.6191.	20+0+12.	0 0
000260	020	178	٠,	20+24ET •	20+122°	0000
	8 20	777	• •	00+0141	.2115-02	
	: 670	122	7 - 0 - 1	20-75-1	2010402	666
	F 60	122	4 0 00	1292+02	1926+02	•
	620	11.		1237+02	1836+02	-6666-
000660	870	60 C		.1184+02	.1750+02	٠
100000	910	100	-36.7	.1133-02	.1670+02	-6666-
101000	013	£ 00	- 100-1	.1085-02	.1597.02	-6666-
10200	011	990	-36.3	•1039•02	-1520+D2	-6666-
103000	011	051	-35.7	10+6+6.	.1460+02	-6666-
10400	013	043	I oppi	10-8250-	20+8051.	- 6666-
105000	013	920	-32-3	10+9216-	. 1 32 0 • 02	•
106000	013	910	remind market	10+1+10	-1262+02	666
107000	. 011	037	# • I M -		20+8021+	* 6
000001	010		8 · CE -		20+4411	*****
000601	110	8 2 0	A-62-	10-101-	20+5011.	
000011	C 20	5 4 4 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	9.87	10+585/-	20+2601	
00011		* 4	9017	10.4/0/-	70.1001.	7 6 7
000211	023	7.00	1010	10+60-0	1046764	, G
114000	200	100 000	-27.9	10-1160-	10.48988.	999
115000	040	3 7 0	-27.2	.5968+01	.8482+01	-6666-
116000	037	25.50	-26.1	.5743+01	. 0097.01	
117000	032	072	-23.5	.5510+01	.7690+01	-6666-
118050	030	8 6 0	-22.1	.5296+01	1357-01	• 6666-
000611	0.00	9 60	3.6.2. 3.6.2.			
000021	900	0 C	0.5.5	47.40		
200021	820	4 60	-22-8		6243+02	6666
123000	013	090	-21.5	4306+0	2	-6666-
124000	010	012	-21.7	.4134+01	.5726.01	6
Ĭ Ž 2000	030	003	-22.5	.3968+01		-6666-
126000	035	5 10	-22.2	• 3809 + 01	87.0	•
127000	032	036	-21.4	_	90	6
2800	028	053	-21.7		663	
2900	027	061	-22-0	_	675+0	666
2000	027	055	-22.0	.3235+01	* 8 4 2 4	
	020		-21.9	_	** 50.6+U.	-4444-
200	033	031	-21.8		132	* 6666-
133000	035	8 M O	-21.7	0	96	6666
	033	# * · ·	-21.6	•		* 6+ 66-
Dons I	028	n,	511.5	9 9	13696461	0000
1 36000	9 20	290	••17-	10+6662.	• C D :	•

METEOROLOGICAL DATA TAPE

HETEOROL ALT	OLOGICAL DATA L'ITTUDE	TAPE	WIND DIRECTION	TEMPERATURE	PRESSURE	DENSITY	DEW POINT
	(FT)	(FT/SEC)	(000)	(DEG C)	(MILLIBARS)	(GRAH/H3)	(1066 C)
	137000	026	990	-21.3	.2431+01	.3363+02	-6666-
	3.8000	030	990	-21.2	.2335+01		.6666-
	139000	032	990	-20.2	.2242+01		-6666-
		033	990	-17.4	•	.2936+01	-6666-
-	0001+1	033	990	D - 1 - 1	•	.2790*01	-6666-
	0002 1	033	690	-12.0	10+9861	*2652+01	
- •	0000 • 1	033	078	0.6-	10+2161	*225Z	
. •		035	08.5	9.9-	10+0+81	_	
•	145000	037	240	0.7	1771+01		
	0009	030	0.60	-4·4	.1705-01	_	.6666-
	0002 • 1	030	107	-3.6	.1641+01	.2121-01	-6666-
	00000	036	11.0	-3.0	.1580+01	.2037.01	-6666-
-7	0006	980	130	-2.0	.1521+01	.1954.01	6666-
	1 \$ 0000	037		-1-1	.1465+01	.1876+01	-6666-
,	151000	035	151	£•-	.1411+01	901.0	-6666-
	1 5 2000	050	161	.2	.1359.01	.1732+01	-6666-
	15 3000	025	174	1	.1309^01	670.0	*6666-
	24000	023	190	9:-	.1261+01	611+0	-6666-
•	155000	021	210	-1.6	.1214.01	.1558-01	-6666-
-	2 5 6 0 0 0	021	239	-2.6	.1169+01	.1505-01	-6666-
	157000	027	248	-2.0	.1126.01	.1446.01	·6666-
:	150000	027	264	-3.4	.1004-01	2	-6666-
	15 9000	020	276	•••	.1043-01	.1355+01	-6666-
	160000	013	250	-5.2	.1004-01	306+0	-6666-
	16 1000	010	50.5	-5.6	00+9996*	.1259+01	-6666-
	162000	015	264	0.9-	.9303+00	.1213+01	-6666-
•	16 3000	027	283	•••-	.8953+00	-1170-01	-6666-
-	164000	032	290	7.9-	.8616+00	.1125+01	-6666-
	165000	033	264	-6.1	.6292+00	.1092+01	-6666-
_	000991	038	260	8·S-	.7981+00	.1040+01	.0666-
	0 000 91	050	244	-7.0	.7681+00	.1005+01	-6666-
-	000091	0\$0	285	9.9-	.7390+00	.9738+00	-6666-
	000691	948	259	•	.7109+00	.9417-00	6666
	170000	035	265	-10.5	. 66 38-00	00+6406	
-	171000	032	234	-10.7	.6577+00	. 8732 • 00	• 6666-
	172000	032	227	-10.6	.6325+00	00+666	
	173000	035	224	-11.1	00++009	00+6900	
. •	174000	110	223	-11.8	.5851+00	00+6411	
2	175000	034	225	~	.5626+00	1512-00	
1	1 76000	043	207	2	00+0196	• •	0000
	17 7000	020	201	຺	25201+00	00+8789+	
	-1	F\$0	8	- 4	00+0005+	. 6 72 1+00	- 6666
-	00047	150	907	•			
	1 8 000 0	n ()	228			D0+#679•	0000
	181000	2 1 0	9 # 2	п 1			
-	•	037	992	٠,	00.4974		0000
. •	9 300	023	246	· 2	0.501	2010	
		035	0	0.11	00+1044		-6666-
		0.90	C 4 6	, ,	1645.0	447340	
	1,76000	7.0	-	-			

- -	MIND SPEED	HIND DIPECTION	TEMPERATURE	PRESSURE	0ENSITY	DEN POINT
(F 1/5t	C	100.61		INTELIBRASI	COLUMN TO THE PERSON TO THE PE	10000
*60	_	205	-12.2	00+5056	00.6/94.	• 6666
601	•	215	-11.9	.3371+00	00.4654.	-6666-
118	_	220	-12.0	.3242+00	** 32*+00	-6666-
133	m	230	-12.6	.3116+00	.4168.00	-6666-
135		234	-13.5	.2998.00	.4022+00	-6666-
130	_	236	-14.3	.2802+00	.3878+00	-6666-
12	_	238	P	2770+00	.3735.00	
11	-	243	-16.3	.2663+00	.3612+00	-6666-
101		246	80° / 11°	00+6552*	00+1646	****
660	•	# S2	6.61-	30+88+2•	003764	
0		257	6.02-	2361+00	.3261+00	*****
101	•	# 52 2	9-22-	00+1927	00.500	*****
106		752	-24.3	2177-00	. 304 7 - 50	
108	•	253	-25.1	00+6002*	00+0467	****
0	_	251	-27.9	2004-002-	2847400	.6666-
	_	246	-28.9	1923+00	.2742+00	6666-
103	•	242	-29.9	.1644-00	.2641+00	-6666-
660	•	244	-31.4	.1768.00	.2548+00	-0666-
100	•	237	-32.3	•1690,000	.2451+00	-0606-
Ξ	36	231	-36.0	.1566.00	.2301+00	-6666-
143	m	231	-36.6	•150 .00	.2209+0C	-6666-
150	0	230	-36.2	.1436+00	.2111+00	-6666-
157		230	-35.2	.1376.00	.1997+00	- 6666-
1	162	230	-34.2	.1319+00	. 1923-00	-6666-
=	165	230	-36.0	1264.00	1857-00	. 6666-
Ξ.	167	231	135.2	1211+00	1773+00	6665-
2	791	257	4.00.1	111000	1656.00	5666-
		7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	0 0	00-11-1		
-	155	0.40	2.01-		1516+00	-6666-
: =	146	24.5	-39.2	.9740-01	.1450+00	-6666-
	38	25.1	9.04-	.9330-01	.1398-00	-6666-
~	26	259	#*6E.	.6930-01	.1331.00	-6666-
=	118	267	1.88.1	.8550-01	. 1269+00	-6660-
-	111	276	0.6E-	10-0618	. 1 22 3+00	* 5666-
= :	801	286	10 to	10-0-11		****
=	101	967		10-06-1	00.6017	*****
٠.	50.0	306	6.	. 7160-01	1097-00	****
	101	3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	A • C • I	10-0199	00.000	9000
00 1	_	320	21.21	10-0259*	00+2501•	* 6666
160	=	326	7-85-	10-0229	00-8001	
ò	0 4 4	331	1.90.4	.5920-61	.9647-01	-6666-
110	_	336	-60.2	10-0-95	Ti-6276*	• • • • • • • • • • • • • • • • • • • •
ð	690	34.2	-60.7	.5340-01	10-624-01	****
ŏ	040	350	-64.2	.5130-01	10-2558	****
ö	052	359	-66.2	10-0-84.	- 0 2 3 H - C 1	* 6666-
ă	04.7	600	-67.2	10-0-94	10-1012	*****
5	5 • 0	016	6.69	10-0 44.	10-13-17	*****
õ	047	030	2-89-	10-017	10-1617	• 6666
9 40	•	038	-69.2	10-0104	10-29-0	- 7 7 7 7 8

DEW POINT	(1066 C)	-6666-	-6666-	-6666-	-6666-	-6666-	-6666-	-6666-	-6666-	-6666-	-6666-	-6666-	-0466-	0666-	-6666-	-6666-	***	-6666-	-6666-	-6666-	-6666-	-6666-	-6666-	-6666-	-6666-	-6666-	-6666-	6666-		.6666-	66661	*****	*****	0000	-6666-	-9999-	-6666-	-6666-	-6666-	-0666-	-6666-	-6666-	-6666-	-6666-	*6666-	-6666-	-6666-	-6666-	-6666-	-6666-
DENSITY	I GRAM/H31	.6544-01	.6265-01	.5999-01	.5746-01	.5507-01	.5265-01	.5028-01	10-8624	. 4 54 0-01	. 4290-01	. 4055-01	.3859-01	.3667-0:	.3502-01	13-454-01	.3212-01	. 3076-01	.2946-01	.2821-01	. 2702-01	.2588-01	.2478-01	.2374-01	.2273-01	.2117-01	.2085-01	10-1661.	-1912-01	.1832-01	1520-01	10-016	10-0710	20-00-6	. 2240-02	6.24 D= D2	.5300-02	.4640-02	*******	.3330-02	.2430-92	.2400-02	.2030-02	.1720-02	.1*60-02	.1230-02	.1030-02	.8690-03	.7320-03	.6150-03
PRESSUPE	IMILIBARS	.3810-01	. 3620-01	.3440-01	.3270-01	.3110-01	.2950-01	.2800-01	.2660-01	.2520-01	.2400-01	.2270-11	ſ	•	*	Ĩ.,	16-60L	.1713-01	.1641-01	.1571-01	.1505-01	1441-01	1380-01	.1322-01	.1256-01	23.2	10-1711.	.1112-01	. 1065-01	.1020-01	.8770-02	. 1530-02	Ú	20-05-0	20-00/5	1500-02	. 3000-02	.2570-02	.2200-02	.1830-02	.1550-02	.1310-02	.1110-02	.9450-0	.8030-03	.6830-03	.5810-03	.4940-03	.4200-03	.3580-03
TEMPERATURE	(10 034)	-10.3	-71.9	-77.4	6-82-	-16.4	-78.0	-79.2	0.08-	-19.8	-78.3	-78.2	-78.2	-78.2	-19.2	-78-6	-18.1	-77.6	-77.0	-76.5	-76.0	-75.5	-74.9	-74.4	-13.9	-73.4	-72.8	-72.3	-71.8	-71.3	-72-3	-13.2	2.4.2	-75.2	-76-2	0 · di	9.00-1	-80.6	-82.0	-82.9	-83.2	-83.6	6.89-	-84.3	-83.9	-82.5	-81.2	-79.8	7.07.	-77.1
MIND DIRECTION	(016)	3.00	6 10	052	053	0.54	950	057	05.7	056	05.5	100	053	053	053	053	053	053	\$ 50	053	053	05.	♦\$0	054	055	055	056	057	050	950	8 00	•01	120	- F	132	• • • • • • • • • • • • • • • • • • • •	0 0	010	986	290	280	. S.	219	271	269	269	269	269	269	26.9
TAPE WIND SPEED	IF TASEC)	052	250	090	90	067	010	910	076	620	280	990	780	1.60	0.02	070	074	010	065	061	057	053	640	5 0	100	036	032	020	024	020	020	220	920	032	035	0.51	200	920	120	***	410	900	022		06.7	7.90	. 900	040	25.0	035
METEOROLOGICAL DATA	16.13	237000	238000	239000	2 4 0000	2 1000	242000	243000	20000	245000	246000	24.7000	246000	249000	250000	251090	252000	2 5 3000	254000	255000	256000	257000	256000	2 6 9000	260000	26 1000	-	26,2000	•	265000	268000	271000	274000	277000	240300	000000		282000	000101	000000	30100		00000	110000	07.05.17	336000	119000	122000	125000	

TATO WATER	110 201		****	-6666-	-6666-	-6666-	-6666-	-0666-	-0660-	-6666-	-0666-	-9999.	-9999.	-6666-	-6666-	-6666-	-6666-	-6666-	-6666-	-6665-	-6666-	-6666-	-6666-	-6666-	-8888-	-6666-
DFRSTTV			. 5160-03	.4330-03	.3630-03	.30*0-03	.2550-03	.2160-03	.1840-03	.1560-03	. 1330-03	.1130-03	.9650-04	-0-00+0.	.7320-04	.6380-04	.5560-0"	*4840-0	*0-052**	.3750-04	.3340-04	.2980-04	.2660-04	.2390-04	.2 50-04	*1940-04
101125 100	1000000		• 30 70-03	.2640-03	.2270-03	.1950-03	.1670-03	1460-03	.1290-03	.1140-03	100-03	. 8830-04	.7760-04	. 7070-04	.6410-04	.5810-04	.5260-D#	4750-04	.4330-04	.3980-0:	.3680-D*	.3400-0*	.3160-04	*0-0*62*	.2740-04	.2570-04
TENDEDATION	1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0301	-72.7	-68.2	-63.7	-59.2	-54.7		5.04	-32.5	-24.6	-16.6	-8.6	2.0	12.6	23.1	37.1	W. **	55.5	67.5	79.0	92.6	105.6	110.9	132.4	146.2
2011-010	201 - 13 - 10 ON 18	19701	268	268	267	267	266	267	266	265	263	260	242	259	255	546	241	226	23 ,	231	226	220	215	209	204	199
MAPE.	12 1/6 6 6 1	1113611	036	240	940	020	053	056	056	056	053	9*0	039	038	037	035	032	029	020	610	610	020	020	120	022	023
ETERMOLUGICAL DA	1001111		331000	334000	337000	34 0000	3 4 3000	346000	349000	352000	355000	358000	36.1000	364000	36 7000	370000	373000	376000	379000	3 6 2000	3.4.50.00	388000	391000	394000	39 7000	00000

METEOROLOGICAL DATA Altitude	TAPE LIND SIEED	WIND DIRECTION	TEMPERATURE	PRESCURE	VENS117	DEW PUINT
(FT)	(F1/SIC)	(05.6)	(OEG C)	INTLLIBARS)	1087XXX	ומנפ כז
000000	000	000	26.0	11073-04	.1182.0*	11.7
000100	016	010	20.1	.9891-03	.1165.04	15.0
00000			T81	60+04644	*D**FILE	0.71
000100	100	010	9.51	.9215.03	.1104.04	
000 400	300	900	8.5.1	.0.0.0.	. 1071.04	-10.6
000 800	015	900	1.01	.6577.03	.1031.04	-1.1
000000	910	015	800	1875-03	. 9 9 8 3 - 0 3	-9.9
00700	50	010	14.7	. 7982-03	.96***03	-7.6
000000	010	900	1210	E0+4-61	6361+03	** :-
000600	017	100	11.3	.7424+03	. 00 18 . 0 3	-6.5
00000	• 10	600	***	.7150-03	. 6762.03	-10.7
000110	210	200	8.2	.6900+03	. 8534+03	-13.7
012000	•	900	40	16650-03	.6273-03	-13.3
0013000	510	010	4.2	.6407-03	. 6036.03	-13.0
000 410	010	+04		10-14141	7807.03	
015000	600	34.5	**	.5941+03	.7594.03	-16.1
	***	28.3	5.4-	.5719-03	.7357.03	
000110	300	236	-2.9	.5503+03	. 7091-03	-25.3
		414	9	.5296-03	.6851.03	-56.2
	300	200	6.65	10+8+05·	.6634.03	-27.9
						-29.1
00000	2	21.1			.6232-03	-30.3
			-12.2	8D+088**	.6048+03	-31.7
000 770		202	. 3	E 0.88 4.	.5850.03	-33.6
00000			9,5,4	FO+1814	.5661.03	-35.6
) C		6-6-	*016+03	.5479-03	-36.7
000460			Ð	11015+83	10++01	38.6
021000	270	66-	-21.7	.3700-03	.5125.03	-39.8
028000	020	197	-23.5	.3550+03	. 4953-03	0.07
029.20	0.18	700	-26.2	.3405+03	. 4 603 + 03	-43.1
000000	021	176	-27.8	.3265+03		~ -
03100	0 30	103	#*O N -	.3129.63	.0.00***	-45.5
032000	0.0	101	-3212	10.0002.	RO+#8#+	
033000	040	189	-35.4	.2871+03	. 4206.03	•
034000	0*0	101	B* 2 5 -	.2748+03	. 00 7 00 0	0.0
035000	041	189		.2629+03	80.08es.	
0 36 000	0*0	300		10.4152.	50102616	
037000	0 40	186	2.77	50.5002.		7 1 1 1
039600	- 660	-501	5 + 5 + 1	50+1622	* D+6266*	
039000	2*0	186	0.83	-2194-03	0.040000	
0000*0	**0	108	?	50.5602.	50.4775	
041000	140	180		50+0±0.2°	500-A515.	4.00
042000	050	189	7.75-	50.9061.	50.3000	7070
00010	150	188	6.7.61	50.00 C	50+6047	200
. 000**0	150 -	. •87	37 · 10 · 1		50.44.6	4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4
0.000	051	067	2.98-	Minter.	50.4592	C - 94 -
000 900	0.50	001	6	50.75	£0.45.7.	
0.47000	050	161	7.00 i	50.001.		1460-
04000	0.5	192	~	MO+3M 3 M 4	5110167	7 9 9 9
000640	670	161	.57.7	.1366.03	5 11 6 6 2 2 .	000

127-03 127-03 127-03 127-03 127-03 128-03	1716675 130203 120103	• 0	(2) (0) (0) (0) (0) (0) (0) (0) (0) (0) (0
	E8+601 FA	9.5	9.000
	10	9.0	1. 9.09-
	= (•••	** 6.09-
	: :	-61.2	1.2
	-		
	•	• • • • • • • • • • • • • • • • • • •	5.29-
	::	51 × 4-	
		2.5	-62.5
	Ī	41	A
	•	•	-61.2
	•	•	• ••••
	•	2.09	2-09-5
	•		
	Ì	, to D	
		-53.5	•
		-51.9	· •
		-50.9	\$
	_	0.0	0.05-
	•		
		-46.6	
		-45.6	54-
		9.6	7
		-13.7	T
!			
	1		4
!		7.44	7070 000
			1
			* *
			1
18 19 19 19 19 19 19 19 19 19 19 19 19 19	1		***
1		-45.0	7
		-45.2	7
		-44.2	7
!		8.24-	•
ļ			**
			1
		-40.6	7
		1.0.1	
		7.05.	681 681
	•	5*8F1	600 T
*1184+62 *1750+02		-37.5	108 -37.5

TABLE 5. (Continued)

THE PROPERTY OF THE PARTY OF TH						92000 TAN
ALTI TUBE	WIND SPEED	MOILDAND DAIR	DEFENDATION OF THE PROPERTY OF	74C 23C4C	TATE MADE	
161	117860	1920)	10101	(M11.10003)		
100000			11050		70.07011	
101000	013	000	7.95-	.1085-02	.1597.02	
102000		886	6286		1520.08	
103000	100	051	-35-7	10.6166.	.1460-02	-4444.
104 000	210	150			1300+02	-1111
10500	500	930	-32.5	.9120-01	.1320.02	-4444
10400	710	984	1916.	10-141-0	.1262-02	•••••
10,000	110	037	-31.4	.0383.01	. 1200 - 02	-6666-
10400	9.6	8.6	206-	10.0600	10.5544	10000
	200		2.0.2	.0101-01	.1103.02	*****
			704	10-F0F4	- 1052+02-	-1111
		• • •	9.2	.7079-01	.1004.02	-000-
			37. 60	10.000 m	10.6294	-000-
11100	02.0	Ē	F-00-100-100-100-100-100-100-100-100-100	10+1140	.9241.01	-111.
- 110000	450	610	44.4	10-5-20-	10.0000	-0000
115000	6		-27.2	10-00-0	.0482-01	-0000-
11000				18703-01		••••-
117000	200	210	4.2.4	.5510.01	.7690.01	-1000-
				10-00251	. 7357-01	-6666-
114000	920	Ē		.8076.01	. 7074-01	-4444-
	96	946	344	10-1404	10-100-	
121000	0.28		-53°	10.4194.	•	-0000-
122000	120	••0	E-4	10-90-4-	10.5.29.	
123000	013	000	-21.5	. 304.01	. 5942.01	••••
124000	010	210		10 · FC I * ·	10.12/5.	*****
125000	030	903	5.22	10+0468	n	
126000	560					
127000	0.32	900	0 · 1 · 1			
128000	820	560				0000
000421	200					1000
20000	720	n - 4				
000161	920		4073	10.000	41.29.001	
19200	679	160	6.16.	2862+01	3968	-000-
00000			•	10-45-4	. 3405+01	-4004-
			• -	10.010.0	3652-01	-4444
14,000		2	•	2533+01	. 3505-01	-0000-
17000	420	440	-21.3	.2431+01	. 9363.03	-0000-
- 1 20 000	93 0	986	4.1	10+96640	. 3220.01	
139000	032	990	-20.2	.2242+01	. 3047+01	••••
14000	033	••0	-17.9	.2153+01	.2930-01	•••••
141000	033	990	-14.9	10.4902.	10+042	****
142000	0 3 3	490	-12.0	10.000.	.2652+01	
143000	033	010	-9.0	. 1912-01	.2522+01	- 6666
144000						
145000	037	240	4.7	. 1771-01	10.4622	****
1000	0.30	#>O	***	10+5011	10+1022	
147000	030	101	9.5	10+11+01	10.1212.	
148000	0 20	• = =	0.5			
00004	5,0	051	-2.0	1822.0	10.1841.	****

100 101		
11264-01 112		
1.6		
11		
1116401		
2.0		
2.0		
10 10 10 10 10 10 10 10		
100 30 11 11 11 11 11 11 11 11 11 11 11 11 11	1 1	
5.6	1 1	200 5 M D 2 D 2 M 6 M 2 M N N N N D D D N
6.6		
10	1 1	0 2 M D 2 D 2 M 0 M 2 M N N N D D 0 D N
6.1	1 1	
6.6	1 1	
6.1	1	
100 100	I	
2.2 2.4 2.4 2.4 2.4 2.4 2.4 2.4 2.4 2.4	ı	
	1	
2.2 2.2 2.2 2.2 2.3 2.4 2.5 2.5 2.5 2.5 2.5 2.5 2.5 2.5 2.5 2.5	1	
2.2 2.2 2.4 2.5 2.5 2.5 2.5 2.6 2.6 2.6 2.6 2.6 2.6 2.7 2.7 2.6 2.6 2.6 2.7 2.7 2.6 2.6 2.7 2.7 2.6 2.6 2.7 2.7 2.7 2.6 2.7 2.7 2.7 2.7 2.7 2.7 2.7 2.7 2.7 2.7		
1.1 1.2 1.2 1.2 1.3 1.3 1.3 1.3 1.3 1.3 1.3 1.3		
1.1 2.2 2.2 2.3 2.4 2.5 2.5 2.5 2.5 2.6 2.6 2.6 2.6 2.7 2.6 2.7 2.6 2.7 2.7 2.7 2.7 2.7 2.7 2.7 2.7		
18.6 18.6		# # # # # # # # # # # # # # # # # # #
		m # # # # # # # # # # # # # # # # # # #
4.5		
0	1	4 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
4.5 4.6		
S		9 49 1
S		•
15.6 16.7		942
	1	6.5
14.2 14.2 15.6 16.6		
14.2		
2.6		70.
2.0		
2.0		70.4
2.0	- 1	
2.6 .2998-00 .4022-00		
3.5		077
3.5		9.0
4.5 .270.00 .313.00 6.3 .270.00 .373.00 7.6 .2869.00 .376.00 6.5 .2869.00 .376.00 6.5 .2869.00 .3261.00 6.5 .2267.00 .3184.00 6.3 .2177.00 .3184.00		# ·
7.6 .2559.00 .3735.00 7.6 .2559.00 .3491.00 9.5 .245.00 .3374.00 2.6 .2267.00 .3384.00 4.3 .2177.00 .3184.00		36
7.8 .2859.00 .3491.00 .3491.00 .3491.00 .3491.00 .3491.00 .3491.00 .3491.00 .3491.00 .3491.00 .3491.00 .3491.00 .3491.00 .3491.00 .3491.00 .3491.00 .3491.00 .3491.00		238
7.8 .2559.00 .3491.00 9.5 .2458.00 .336.00 0.9 .2267.00 .3154.00 4.3 .2177.00 .3164.00	ı	
9.5 .24500 .3374.00 2.6 .2267.00 .3261.00 4.3 .2277.00 .3047.00		. 4
7.5 . 2.861.00 . 3.861.00 . 3.861.00 . 3.861.00 . 3.861.00 . 3.861.00 . 3.861.00 . 3.861.00 . 3.861.00		D 4
2.8 .2267+00 .3154+00 .3154+00 .4.3 .2177+00 .3047+00		754
6- 00+2:50E: 00+2:72: 8:7		~ (
1.2 DE . DO+1715. S.4		20
		5.7

TABLE 5. (Continued)

THE DER POINT	1056 C)	-0000	•64.	-6666		*****	-0000-	-0000-	-6466-			.0000		6666	••••		-0000-	-6666-	-0000-	- 4666-	••••	2000	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •			-0000		******	-6666-	• • • • • • •	.0000					*4464	.0000	-6666-	-6006-	-0000-	-0000-	• • • • • •		• • • • • • • • • • • • • • • • • • • •			• 6666-
DENSITY	へのエノエマロロ	00+04631	.2847.00	00.3464	.2641.00	2540+00.	2451+00	2301+00	0++0	00+11+4			00+4584	1773-00	1714+00	98-9694	.1569.00	- 1516.00	.1450+00	- 00+86£ E	1331+00	0011011	.1223+00		1163-00		1077-00	00.400	10-2440	. 7224-01	10-4290	352-01	3	10-+00'·	10-1851			4265-01	10-6665.	ş	.5507-01	.5265-01	10-0205				TO GEODA	10-6585.
	C# 10010000	x2080+01	.2004+00	20 4 44 1	-10++00	21763. BO	00+040		00+00\$1	15 36 - 00	004961		- 5.26 C + 120	00+412.1	7 146+00	30 -5444	00:1961	1016-00	.9790-01	· 40-0KK4	10-0640		10-04-TO.		10 0446	: 10.001.0 : .	10-019	10-0-0		10-01-91		.5130-01	-0000	20-0994·				2480-01	. 240-01	.3270-01	.3110-01	.2950-01	.2000-01		2520-01	10-00-2	٧,	.2160-01
TEMPERATURE	1056 C1	4162	-27.0		-29.0	2275-	-32.3		4.4						7	\$	-10.7	2065	-39.2		-30.0	200	0.0 N-		0.00	604 G	0.55-			-60-2	200	-0.5	449	-67.2			M . U	4 6	-73.4		-16.4	-76.0	-79.2		8.67			-7862
	(910)		251	246	2 2		23.7		211	230			210		****		912	048	228	164 :-	25.9	-	276	•		• R	• 15 • 15	766		999	N. P.	350		8	P (0			• 2	052	053	- SC	056	750		# 10 C	0 0 0 0	100	023
1A TAPE ETED SPEED	•	801	801	110	801	660	901	9 PM	7.0					187		561	162		9	130	126		111	801	**************************************	Pi (101	140		220	600	090	250	242	5 P		2 C		9 0	***	190	010	# P D		620	7 20 0	9 5	
METEOROLOGICAL DATA Altitude	(FT)	200000	201000	202000	20300	204000	205000	206000				00000			213000		215000	214000	217000	218000	219000	- 22000g	221000	222000	223000	224 000	225000	200922	000127	200000	230000	231000	- 535 000	233000	234000	235000	000017	25000	239000	240000	24,1000	242000	243000	000442	245000	246000	24/000	246000

TABLE 5. (Concluded)

2 · · · · · · · · · · · · · · · · · · ·
1088177 15884/#30 16380-04 16380-04 16380-04 16380-04 16380-04 1640-04 1660-04 1660-04 1660-04 1660-04
PRF 55 URE
17 MPC PATURE 2 1-1 2 1-1 3 5-7 4 5-5 7 5-5 7 0-0 9 7-0 11 11 1-0 1 11 1-0 1 11 1-0
MAD DIRECTION CTES CON CTES CON CTES CON
DAIA TAFE 1 F 7 SEC 1 1 F 7 SEC 1 1 F 7 SEC 1 1 5 C 1 1 C 1
ME TE DROLOGICAL DA ALTITURE 1871 375000 375000 375000 387000 387000 387000 387000 387000 391000 391000 391000 391000

TABLE 6. STS-1 SRB DESCENT-IMPACT SURFACE SHIP OBSERVATIONS

Site: USN Ship, Gen. H.S. Vandenberg

Location: 30°N Latitude 78°W Longitude

Date: April 12, 1981 Time: 1212 Z

Surface Observation:

E :: +						į
Air Temp. Jr	Wel-Builo or	Dew Pt. vr	Pressure mb	wind Dir.	•	wind Sp. Kt.
71.8	63.8	59	1024.1	140°		7
Sky Observation:						
		Total Sky			Visibility	
Clouds		Cover		Sky	(miles)	
2/10 Cumulus at		6/10	2/10	0	7	
3/10 thin cirrus	s at 35000 ft					
Sea Observations:						
Sea Condition:		Wind Waves:	Swell Conditions:	itions:		
Sea Slight - Code 3	de 3	Freq. Ht.	Dir. from			
0/10 Breaking waves	waves	Sec. m.	Swell is coming		Sec. m.	
0/10 Foam		2	010		8	
Surface Sea Wat	Surface Sea Water Temp = 72°F					




Figure 1. Surface weather map at launch of STS-1




Figure 2. 500 mb map at launch of STS-1.




Figure 3. GOES SMS-II IR imagery of cloud cover at launch time of STS-1 (1200Z, 12 April 1981),



Enlarged view of GOES SMS-II visible imagery of cloud cover with exhaust transvisible during lagrach of STS-1 (12002, 12 April 1981). Figure 4.






Figure 5. Scalar wind speed and direction at launch time of STS-1.



STS-1 prelaunch/launch limsphere...easured in-plane component winds. Figure 6.

IN-PLANE COMPONENT WINDS
JIMSPHERE PROFILES



OUT-OF-PLANE COMPONENT WINDS
JIMSPHERE PROFILES

Figure 7. STS-1 prelaunch/launch Jinsphere-measured out-of-plane component winds.




Figure 8. STS-1 temperature profile versus altitude for launch (left) and SRB descent (right).

7 4




Figure 9. Scalar wind speed and direction for SRB descent.

REFERENCES

- 1. Saturn Flight Evaluation Working Group: Saturn Launch Vehicle Flight Evaluation Report Appendix A Atmosphere (A separate report is prepared for each Saturn Vehicle launch operation). George C. Marshall Space Flight Center, Alabama.
- 2. Johnson, D.L.: Summary of Atmospheric Data Observations for 155 Flights of MSFC/ABMA Related Aerospace Vehicles. NASA TM X-64796, December 5, 1973.
- 3. Johnson, D.L.: Atmospheric Environment for ASTP (SA-210) Launch. NASA TMX-64990, February 1976.
- 4. Justus, C.G., et al.: The NASA/MSFC Global Reference Atmosphere Model Mod 3 (with Spherical Harmonic Wind Model), NASA CR-3256, March 1980.

APPROVAL

ATMOSPHERIC ENVIRONMENT FOR SPACE SHUTTLE (STS-1) LAUNCH

By D.L. Johnson, G. Jasper, and S.C. Brown

The information in this report has been reviewed for technical content. Review of any information concerning Department of Defense or nuclear energy activities or programs has been made by the MSFC Security Classification Officer. This report, in its entirety, has been determined to be unclassified.

ROBERT E. TURNER

Chief, Environmental Applications Branch

WILLIAM W. VAUGHAN

CHARLES A. LUNDOUIST

Chief, Atmospheric Sciences Division

Director, Space Sciences Laboratory